

MICRÓFONOS INALÁMBRICOS

MICRÓFONO INALÁMBRICO DE DIADEMA PARA AEROBIC

MI-MAU16

Micrófono de diadema para aeróbic, con captación de voz de alta calidad, aislamiento frente ruidos y elevada ganancia antes de la realimentación. Peso ligero para disponer de libertad de movimientos y gran comodidad gracias a su diseño ergonómico. Conectado al transmisor tipo petaca incluido se convierte en micrófono inalámbrico.



CARACTERÍSTICAS GENERALES Sistema de microfonía inalámbrica

- Banda de frecuencias 823 ~ 832 MHz y 863 ~ 865 MHz.
- Configuración automática
- Display en todos los transmisores y receptores
- Sin interferencias con 4G
- Hasta 15 micrófonos simultáneos
- Receptores de 1 y 2 canales diversity
- Micrófonos de mano, de solapa, de diadema, de aeróbic y de sobremesa

Especificaciones técnicas

micrófono

Conector	4-pin mini XLR
Respuesta en frecuencia	60 Hz ~ 15.000 Hz
Diagrama polar	Omnidireccional
Sensibilidad (a 1KHz)	-64 ± 3 dB (0,63 mV)
Impedancia	1,8 kΩ
Máx. SPL para 1% THD	130 dB



transmisor

Modo de oscilación	Phase-locked loop (PLL)
Rango de frecuencia	470 ~ 960 MHz
Ajuste remoto	Por ultrasonidos
Potencia RF	10 mW / 50 mW
Estabilidad RF	< ±10 kHz @ Fc
Modulación cambio de frecuencia	± 48 kHz
Radiación armónica	< -50 dB
Funciones	Mute, auto apagado, atenuación de entrada, sensibilidad, batería baja LCD + LED
Monitorización mediante	Mini XLR 4 pin
Puerto de entrada	Encendido, mute, grupo, canal, frecuencia, sensibilidad, atenuación de entrada, auto apagado
Controles	2 Pilas AA alcalinas o recargables
Batería	Si
Carga	Si
Dimensiones (mm)	62 (ancho) x 97 (alto) x 20 (largo)



WIRELESS MICROPHONES

DOUBLE EAR-HOOK WIRELESS MICROPHONE FOR AEROBIC

MI-MAU16

Double ear-hook microphone for aerobic, with high-quality voice pick-up, excellent gain-before-feedback and noise isolation. Lightweight benefits great freedom and mobility and ergonomic design ensures comfortable wearing. Connected to the included bodypack transmitter it becomes a wireless microphone.



MAIN FEATURES

Wireless microphone system

- Frequency band :823 ~ 832 MHz and 863 ~ 865 MHz.
- Automatic configuration
- Display on transmitters and receivers
- No interference with 4G
- Up to 15 simultaneous microphones
- Receptors of 1 and 2 channels with diversity
- Hand-held, lavalier, stage, aerobic and desk microphones

Technical specifications

microphone

Connector	4-pin mini XLR
Frequency Response	60 Hz ~ 15,000 Hz
Polar Pattern	Omnidirectional
Sensitivity (at 1KHz)	-64 ± 3 dB (0.63 mV)
Impedance	1.8 kΩ
Max. SPL for 1% THD	130 dB



transmitter

Frequency Oscillation Mode	Phase-locked loop (PLL)
Carrier Wave Frequency Range	470 ~ 960 MHz
Remoset Frequency	Ultrasonic
RF Power Output	10 mW / 50 mW
RF Stability	< ±10 kHz @ Fc
Modulation Frequency Shift	± 48 kHz
Harmonic Radiation	< -50 dB
Functions	Mute, auto off, input level attenuation, sensitivity adjustment, low power indication
Display By	LCD + LED
Input Port	4 pin Mini XLR
Controls	Power, mute, group, channel, frequency, sensitivity adjustment, input level attenuation, auto off
Battery	AA alkaline or rechargeable battery x 2
Charging	Yes
Dimensions (mm)	62 (W) x 97 (H) x 20 (L)

